

9RJ1-076A-TFD

HCFC, R-22, 60 Hz, 3 -Phase, 460 V

Medium Temperature



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	20	0
Condensing Temp. (°F)	120	110
Return Gas Temp. (°F)	65	50
Liquid Temp. (°F)	120	95
Capacity (Btu/hr)	64000	41500
Power (W):	8500	6600
Current (Amps):	14.10	11.90
EER (Btu/Wh):	7.50	6.30
Mass Flow (lbs/hr):	940	570
<u>Sound Data @</u>		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	0.0 Max
Record Date:	2006-12-21	

Mechanical

Displacment(in ³ /Rev):	22.56
Displacment(ft ³ /hr):	1370.78
Overall Length (in):	25.72
Overall Width (in):	15.06
Overall Height (in):	17.59
Mounting Length (in):	15.00
Mounting Width (in):	12.00
Mounting Height (in):	18.63 *
Suction Size (in),Type:	1 3/8 Sweat
Discharge Size (in),Type:	1 1/8 Sweat
Initial Oil Charge (oz):	115
Oil Recharge (oz):	105
Net Weight (lbs):	294.0
Internal Free Volume (in ³):	
Horse Power:	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical

LRA-High*(Amp):	82.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	19.0
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	13.6
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	12.2
RPM:	
UL File No:	SA-2337
UL File Date:	1972-04-26
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

Capacitors

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-22 HCFC	380/400	3	50	Medium Temperature
R-12 CFC	380/400	3	50	UL Medium Temp
R-502 CFC	460	3	60	Medium Temperature
R-502 CFC	460	3	60	Low Temperature
R-502 CFC	380/400	3	50	Medium Temperature
R-502 CFC	380/400	3	50	Low Temperature