

FFAP-015Z-CFV-072

HFC, R-134a, 60Hz, 1- Phase, 208/230 V



Availability : Standard US Wholesaler

Mechanical

Unit Height (in):	16.6
Unit Length (in):	24.1
Unit Width (in):	18.3
Ship Weight (lbs):	110.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.375
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	25

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	13.9
Compressor:	ZS09KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	40.3
Compressor LRA - Half winding:	
Compressor RLA:	10.0
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	25-Aug-2017	Return Gas Temp. (°F):	40
Compressor:	ZS09KAE-PFV-118 x 1	Subcooling (°F):	5
Performance No:	13624	Air Flow Rate (CFM)	1070

90°F Ambient Air Temperature

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
-10	3,250	97.0	7.0	4.3
-5	3,730	97.9	7.9	4.8
0	4,250	98.8	8.8	5.3
5	4,800	99.9	9.9	5.8
10	5,400	101.0	11.0	6.3
15	6,040	102.2	12.2	6.9
20	6,730	103.4	13.4	7.5
25	7,480	104.8	14.8	8.1