

FFAP-060Z-TFC-071

HCFC, R-22, 60Hz, 3- Phase, 208/230 V



Availability : Custom US OEM Or Wholesaler

Mechanical

Unit Height (in):	26.6
Unit Length (in):	28.3
Unit Width (in):	44.1
Ship Weight (lbs):	320.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.5 SWEAT
Suction Connection Size (in)/Type:	1.125 SWEAT
Discharge Line Size(in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	64

Electrical

Max Fuse Size:	50
Min Circuit Ampacity:	33.5
Compressor:	ZS45K4E-TF5-250
Compressor LRA - Low:	
Compressor LRA - High:	156.0
Compressor LRA - Half winding:	
Compressor RLA:	23.9
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	06-Dec-2017	Return Gas Temp. (°F):	40	
Compressor:	ZS45K4E-TF5-250 x 1	Subcooling (°F):	5	
Performance No:	13452	Air Flow Rate (CFM)	4240	
90°F Ambient Air Temperature				
Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
15	42,200	113.1	23.1	7.5
20	46,300	115.2	25.2	7.9
25	50,500	117.3	27.3	8.3
30	55,500	119.6	29.6	8.7