

M6JM-H043-IAA-179

HFC, R-404A, 60Hz, 1- Phase, 115 V



Availability : Standard US OEM

Mechanical

Unit Height (in):	9.7
Unit Length (in):	14.0
Unit Width (in):	11.5
Ship Weight (lbs):	39.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.25 SWEAT
Suction Connection Size (in)/Type:	0.375 SWEAT
Discharge Line Size(in):	0.25
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	12

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	13.2
Compressor:	ASE39C5E-IAA-103
Compressor LRA - Low:	
Compressor LRA - High:	47.0
Compressor LRA - Half winding:	
Compressor RLA:	10.0
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	0.36
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	11-Jan-2017	Return Gas Temp. (°F):	40
Compressor:	ASE39C5E-IAA-103 x 1	Subcooling (°F):	5
Performance No:	10957	Air Flow Rate (CFM)	201

90°F Ambient Air Temperature

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
-5	2,560	113.0	23.0	4.0
0	2,730	114.7	24.7	4.0
5	2,950	116.6	26.6	4.0
10	3,210	118.9	28.9	4.1
15	3,510	121.4	31.4	4.2
20	3,830	124.2	34.2	4.3
25	4,170	127.1	37.1	4.4
30	4,510	130.1	40.1	4.5