

M6PL-0052-IAA-177

HFC, R-404A, 60Hz, 1- Phase, 115 V



Availability : Standard US OEM

Mechanical

Unit Height (in):	11.2
Unit Length (in):	19.9
Unit Width (in):	11.1
Ship Weight (lbs):	46.0
Condensor Type:	
CopeVap Water Storage:	
Liquid Connection Size (in)/Type:	0.25 SWEAT
Suction Connection Size (in)/Type:	0.375 SWEAT
Discharge Line Size(in):	0.25
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	12

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	8.5
Compressor:	AFE20C5E-IAA-103
Compressor LRA - Low:	
Compressor LRA - High:	40
Compressor LRA - Half winding:	
Compressor RLA:	6.3
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	0.36
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	11-Jan-2017	Return Gas Temp. (°F):	40
Compressor:	AFE20C5E-IAA-103 x 1	Subcooling (°F):	5
Performance No:	10350	Air Flow Rate (CFM)	201

90°F Ambient Air Temperature

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
-25	1,550	105.4	15.4	3.3
-20	1,770	107.0	17.0	3.5
-15	2,000	108.7	18.7	3.7
-10	2,240	110.6	20.6	3.8
-5	2,490	112.6	22.6	4.0
0	2,740	114.7	24.7	4.1
5	3,010	116.9	26.9	4.2
10	3,270	119.2	29.2	4.2
15	3,540	121.7	31.7	4.2