SAFETY DATA SHEET

DP 2515 WHITE, WATER BASED PROTECTIVE COATING

PRODUCT NAME: WHITE. WATER BASED PROTECTIVE COATING

PRODUCT CODE: DP 2515

MANUFACTURERS' NAME: DESIGN POLYMERICS

ADDRESS: 3301 W. Segerstrom Ave.

Santa Ana, ČA 92704

EMERGENCY PHONE: Chem-Tel: (800) 255-3924 (24 Hrs)

BUSINESS HOURS: 7:30am – 4:30pm PT

CONTRACT NUMBER: MIS0005056 REVISION DATE: March 15, 2018 INFORMATION PHONE: (714) 432-0600

REVISION #: 8.0

PREPARED BY: Technical Dept. Supersedes all previous DOT HAZARD CLASS: Not Hazardous UN Number N/A

SHIPPING NAME: N/A Packing Group N/A

TAMMABILITY

TAMMABILITY

REACTIVITY

B

PROTECTIVE
EQUIPMENT

HMIS Health Hazard

Reactivity

Personal Protection

========= SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION ==============

REPORTABLE COMPONENTS

CAS NUMBER

VAPOR PRESSURE mm Hg @ TEMP

WEIGHT PERCENT

Page: 1

0

0

В

None

CAS#	Trade secret Y/N	Chemical Name	Comment
Proprietary Blend	YES		

INHALATION: Remove to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, administer artificial respiration. Contact physician or emergency medical facility immediately.

SKIN: Remove contaminated clothing and shoes. Wash exposed area thoroughly with soap and water for at least 15 minutes. Do not rub affected area. If irritation persists, get medical attention. Skin reaction may take 24 to 48 hours to develop. Wash contaminated clothing before reuse.

EYES: Immediately flush eyes with large amounts of water for at least 15 minutes while frequently lifting the upper and lower eyelids. If irritation persists, call a physician.

INGESTION: Do not induce vomiting. Contact physician or emergency medical facility immediately. Never give anything by mouth to an unconscious person.

FLASH POINT: Not Applicable METHOD USED: Not Applicable

FLAMMABLE LIMITS IN AIR BY VOLUME – LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: The product will only burn after the water it contains is driven off. For dried film use water, foam, carbon dioxide or dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: When dried film burns, carbon dioxide (CO₂), carbon monoxide (CO), and smoke are produced. Firefighters should wear self-contained breathing apparatus, especially in enclosed areas. Cool containers and minimize vapors with water spray.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers exposed to high temperatures may explode or burst due to build-up of steam pressure.

SAFETY DATA SHEET

DP 2515 WHITE, WATER BASED PROTECTIVE COATING

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike, contain, or absorb with inert absorbent material. Collect spilled material in a salvage container. Prevent spill from entering sewers, drains, streams, waterways, or other bodies of water.

WASTE DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: **DO NOT ALLOW TO FREEZE.** Store in a cool dry location away from heat. Keep containers tightly closed and store with adequate ventilation.

OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. Avoid inhalation of excess vapors, ingestion, and unnecessary, prolonged, or repeated contact with this and any other chemical. Change soiled work clothes frequently. Clean hands after handling. KEEP OUT OF REACH OF CHILDREN.

========= SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION ==========

RESPIRATORY PROTECTION: Not required under normal conditions. Provide sufficient ventilation to maintain constant fresh air in workspace. If TLV is exceeded, use NIOSH/MSHA approved organic vapor and mist, supplied air, or self-contained breathing apparatus. Avoid breathing sanding dust.

VENTILATION: Use adequate mechanical (general and/or local) ventilation to maintain exposure below TLV.

SKIN PROTECTION (PROTECTIVE GLOVES): Wear resistant gloves such as polyethylene.

EYE PROTECTION: Use chemical splash goggles or OSHA permitted safety glasses.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Wear impervious clothing. Eye wash station.

WORK / HYGENIC PRACTICES: Source of clean water should be available for flushing eyes and washing skin. Wash thoroughly after handling any chemicals, especially before eating, drinking, or smoking. Remove and launder contaminated clothing before reuse.

COLOR: White

PHYSICAL FORM: Mobile Liquid ODOR: Mild, sweet SOLUBILITY IN WATER: Miscible BOILING POINT: 212°F

FREEZING POINT: 32° F (0° C) COATING V.O.C.: 4.5 g/l pH: 8.0 - 9.5SPECIFIC GRAVITY ($H_2O=1$): 1.2 - 1.3% VOLATILES BY WEIGHT: 35-45VISCOSITY (cps): approx. 3,500-4,500

STABILITY: Stable at ambient temperatures.

CONDITIONS TO AVOID: Coagulation may occur after freezing, thawing, or boiling.

INCOMPATIBILITY (MATERIALS TO AVOID): Metal salts, mineral acids (i.e. sulfuric, phosphoric, etc.) Strong oxidizing agents. Strong reducing agents.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: May form toxic materials on thermal decomposition including Carbon monoxide (CO), Carbon dioxide (CO₂), and various hydrocarbons. Under fire conditions, this product will release hydrogen chloride gas.

This product is considered non-hazardous under the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Page: 2

SAFETY DATA SHEET

Page: 3

DP 2515 WHITE, WATER BASED PROTECTIVE COATING

SECTION XII – ECOLOGICAL INFORMATION Ecotoxicity: No ecotoxicity date was found for the product Environmental Fate: No environmental information found for this product Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines **DOT Hazard Class** Not Hazardous **UN Number** N/A Shipping Name N/A Packing Group N/A

EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW (SARA TITLE III):

Section 311/312 Categorizations (40 CFR 370): Immediate (Acute) Health Hazard.

Section 313 Information (40 CFR 372) – Toxic Chemicals List: No components of this product are present in quantities above "deminimus" levels.

Toxic Substances Control Act (TSCA): All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

CERCLA INFORMATION (40cfr 302.4): Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

CALIFORNIA PROPOSITION 65 (Safe Drinking Water and Toxic Enforcement Act of 1986): None listed

MSDS Creation Date: April 9, 2015
MSDS Revision Date: March 15, 2018
MSDS Revision Notes: Date Change

MSDS Author: Technical Department

Disclaimer: The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Design Polymerics from its suppliers, and because Design Polymerics has no control over the conditions of handling and use, Design Polymerics makes no warranty, express or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Design Polymerics assumes no responsibility from use or reliance thereon. It is the responsibility of the user of Design Polymerics products to comply with all applicable Federal, State and Local Laws and Regulations.