



# FASCO Motor Scope Selection Guide

## SHADED POLE MOTORS - 4.4" DIAMETER (cont.)

FASCO MODEL#	DIA.	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.
D656	5	1/8	230	1050	1	2.1	Open Vent.	CW	SLV	1/2 X 3-7/8
D164	5	1/6-1/8-1/10-1/2	115	1050	4	6.5-4.8-4.3-3.7	Open Vent.	CW	SLV	1/2 X 4-1/2
D224	5	1/6-1/8-1/12	230	1050	3	3.2-2.3-1.8	Open Vent.	DS	SLV	10 X 1/2 X 10
D318	5	1/6-1/8	230	1050	2	3.1-2.2	Open Vent.	CW	SLV	1/2 X 3-1/2
D166	5	1/6-1/9	115	1050	2	7.2-3.8	Open Vent.	CW	SLV	1/2 X 3-1/2
D156	5	1/6	115	1050	1	6.6	Open Vent.	CW	SLV	1/2 X 3-7/8
D240	5	1/6	115	1050	1	6.2	Open Vent.	CW	SLV	1/2 X 3-1/2
D658	5	1/5-1/6-1/7-1/8	208-230	1050	4	4-3.4-3.1-2.4	Open Vent.	CW	SLV	1/2 X 5-1/4
D158	5	1/5-1/6-1/7	115	1050	3	6.7-5.3-4.7	Open Vent.	CW	SLV	1/2 X 4-1/8
S156	5	1/3	115	1050	1	6.6	Open Vent.	CW	SLV	1/2 X 3-7/8
D177	5	1/10-1/20	115	1050	2	3.9-1.7	Open Vent.	CCW	SLV	3/8 X 3-5/8
D1066	5	1/10	115	1050	1	3.6	Open Vent.	CW	SLV	1/2 X 2-3/4
D1028	5	1/8	115	1050	1	3.3	Open Vent.	CW	SLV	1/2 X 2-1/2

## SPLIT PHASE MOTORS

FASCO MODEL#	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.
D6002	1/4	115 / 230	1725	1	5.2-2.6	Open Drip Proof	REV	BALL	1/2 X 1-1/2
D6004	1/3	115 / 230	1725	1	6.2-3.1	Open Drip Proof	REV	BALL	1/2 X 1-1/2
D6006	1/2	115 / 230	1725	1	8.6-4.3	Open Drip Proof	REV	BALL	1/2 X 1-1/2