# FRESH-AIRE UV. AHU SERIES 1 INDOOR AIR QUALITY INNOVATION

The **Fresh-Aire UV® AHU Series 1** germicidal UV light system for central air systems features a robust design, durable construction and water-resistant components.

The auto-switching 120-277 VACpower supply is completely sealed for mounting in wet locations. In addition, the UV lamp cables incorporate a waterproof connector design with a 6' lead to allow safe routing of cables within the air handler.

The power supply is available with an optional 120 VAC plug.



- Water resistant shielded lamp design for stable UV operation
- Electronic high efficiency ballast design for optimum lamp performance
- Automatic input voltage selection from 120 - 277 VAC 50/60 Hz.
- Lifetime power supply Warranty!

#### **BENEFITS**

- Reduces household odors, germs and viruses from the air space.
- Eliminates mold, mildew and fungus growth in the air handler.
- Prevents slime build up in the drain pan
- Improves air handler system efficiency and performance.



**UV LAMP OPTIONS** 



2 YEAR LAMP



**ODOR CONTROL** 

Single - Dual - Triple - Quad Lamp Options







Installation of **Fresh-Aire UV™** systems has never been easier! Our revolutionary new **Magnetic "Z" Bracket** eliminates the need for drilling, precise measuring, and fumbling with small screws in the tight confines of the air handler - in fact no tools are required at all to install the bracket!



Manufactured by Triatomic Environmental, Inc. WWW.FRESHAIREUV.COM sales@freshaireuv.com 800-741-1195





# FRESH-AIRE UN

# **AHU SERIES 1**

## **UV LIGHT DISINFECTION SYSTEM**

### **Specifications & Part Numbers**

AHU Series 1 with One Year Lamp(s)

TUV-100S-I (single) TUV-100D-I (dual)

ADD "P" for wall plug Example: TUV-100S-I-P

TUV-100T-I (triple)

TUV-100Q-I (quad)

TUV-100S-I-OS (single, odor control)

TUV-100D-I-OS (dual, odor control)

TUV-100T-I-OS (triple, odor control)

TUV-100Q-I-OS (quad, odor control)

AHU Series 1 with Two Year Lamp(s)

TUV-200S-I (single) TUV-200D-I (dual)

ADD "P" for wall plug Example: TUV-200S-I-P TUV-200T-I (triple)

TUV-200Q-I (quad)

TUV-200S-I-OS (single, odor control)

TUV-200D-I-OS (dual, odor control)

TUV-200T-I-OS (triple, odor control)

TUV-200Q-I-OS (quad, odor control)

TUVP-1S/1D-I (single & dual) power supply specs

Electrical Auto switching multi-voltage

0.51A /120V Thru 0.22A /277V

**Dimensions** 8.75"L x 3.5" W x 2.5"D

TUVP-1T/1Q-I (triple & quad) power supply specs

Electrical Auto switching multi-voltage

1.02A /120V Thru 0.44A /277V

**Dimensions** 13"L x 3.5" W x 2.5"D

1 Year UV lamp TUVL-100 specs

Spectrum 100% 254 NM Germicidal UV-C **Unshielded Quartz Hot Filament** Type

**Dimensions** 15"L x 0.74" Dia.

2 Year UV lamp TUVL-200 specs

100% 254 NM Germicidal UV-C Spectrum **Shielded Quartz Hot Filament** Type 15"L x 1" Dia. **Dimensions** 

Odor control UV lamp option (OS)

Spectrum 90% 254 NM Germicidal UV-C

10% 185 NM Odor Oxidation

Common to all

Weight 4 lbs.

Kit Includes Internally Mountable Power Supply, 6'

Lamp Cable, 6' Power Cord, UV Lamp(s), Lamp Mounting Brackets, Mounting

Hardware and Panel Indicator



Choose locations inside the air system where single, dual, triple, or quad Fresh-Aire UV® Series 1 lamp(s) will provide optimum coverage, or, place the lamp where mold growth is most evident.

Available From:		

