

FLEXX

PROVIDES **OUTDOOR AND INDOOR FLEXIBILITY WITH COMFORT.**



G R E E C O M F O R T . C O M

- HORIZONTAL DISCHARGE AIR ON OUTDOOR UNIT
- ULTRA HEATING & COOLING CAPABILITIES
- CONVENTIONAL, 24 VAC THERMOSTAT CONTROL
- HIGH EFFICIENCY, UP 20 SEER / 10.5 HSPF

WHEN YOU WANT TO FLEXX

With GREE's EVI Inverter Technology and horizontal discharge, the FLEXX delivers up to 20 SEER efficiency in a smaller, quieter footprint. The FLEXX is ideal for add-on replacements and new construction with ULTRA heating & cooling capabilities.

- High efficiency, up to 20 SEER / 10.5 HSPF
- Cooling range: 5 °F - 129 °F
- Heating range: -22 °F - 75 °F
- Sound levels down to 45 dB(A) on outdoor unit
- Horizontal (side) discharge on outdoor condenser
- Conventional, 24 VAC thermostat control
- Eco-friendly R410A refrigerant

SYSTEM TYPE		HEAT PUMP			
Outdoor Model		FLEXX36HP230V1A0		FLEXX60HP230V1A0	
Indoor Model		FLEXX24HP230V1AH	FLEXX36HP230V1AH	FLEXX48HP230V1AH	FLEXX60HP230V1AH
SYSTEM PERFORMANCE					
Cooling Capacity	Btu/h	24000	36000	48000	54000
Heating Capacity	Btu/h	24000	36000	48000	54000
SEER / EER		20 / 12.5	18 / 11	18 / 11	17 / 10.5
HSPF		10.5	10	10.5	10
Cooling Temperature Range	°F	5 - 129		5 - 129	
Heating Temperature Range	°F	-22 - 75		-22 - 75	
Refrigerant Type		R410A			
OUTDOOR UNIT DATA					
Power Supply	VAC	208/230V / 1Ph / 60 Hz	208/230V / 1Ph / 60 Hz	208/230V / 1Ph / 60 Hz	208/230V / 1Ph / 60 Hz
Sound Pressure Level	dB(A)	62		61	
Control Voltage	VAC	24		24	
Rated Current Cooling	A	21		28	
Rated Current Heating	A	25		31	
MCA	A	24		35	
MOCP	A	35		45	
External Dimensions (W x H x D)	in	37 x 32 1/4 x 18 1/8		42 3/4 x 53 3/4 x 14 1/2	
Net Weight	lbs	217		308	
Gross Weight	lbs	240		337	
INDOOR UNIT DATA					
Power Supply	VAC	208/230V / 1Ph / 60 Hz	208/230V / 1Ph / 60 Hz	208/230V / 1Ph / 60 Hz	208/230V / 1Ph / 60 Hz
Sound Pressure Level	dB(A)	45	49	50	51
Control Voltage	VAC	24	24	24	24
Rated Current Cooling	A	2.1	2.1	3.2	3.2
Rated Current Heating	A	2.1	2.1	3.2	3.2
MCA	A	4	4	4	4
MOCP	A	15	15	15	15
MCA w / Optional 5, 8, 10 kW Electric Heater	A	See submittal's for MCA values for the 5, 8, 10 kW heaters		-	-
MOCP w / Optional 5, 8, 10 kW Electric Heater	A	See submittal's for MCOP values for the 5, 8, 10 kW heaters		-	-
MCA w / Optional 10, 15, 20 kW Electric Heater	A	-	-	See submittal's for MCA values for the 10, 15, 20 kW heaters	
MOCP w / Optional 10, 15, 20 kW Electric Heater	A	-	-	See submittal's for MCOP values for the 10, 15, 20 kW heaters	
Air Flow	CFM	940	1000	1470	1600
External Static Pressure	In W.c.	0.4	0.4	0.4	0.4
Dehumidification	pt/hr	6.03	9.68	9.94	13.29
External Dimensions (W x H x D)	in	21 1/4 x 48 1/4 x 21 1/4	21 1/4 x 48 1/4 x 21 1/4	24 3/4 x 57 1/4 x 21 1/4	24 3/4 x 57 1/4 x 21 1/4
Net Weight	lbs	156	156	202	202
Gross Weight	lbs	169	169	218	218
REFRIGERANT PIPING					
Line Set Size (Liquid - Gas)	in	3/8 - 3/4	3/8 - 3/4	3/8 - 3/4	3/8 - 3/4
Pre-Charge Length	ft	25	25	25	25
Pipe Length (Min / Max)	ft	15 / 98	15 / 98	15 / 98	15 / 98
Max. Pipe Elevation	ft	49	49	49	49
LIMITED WARRANTY		5 Years Parts and Compressor - Residential			



Specifications are subject to change without notice. Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice or without incurring obligations. ©2020. All rights reserved.