# PRODUCT SPECIFICATIONS

PAGE 1 OF 1

## STANDARD CONSTRUCTION

#### FRAME

0.032" THICK, ROLL FORMED ALUMINUM (0.045" THICK EXTRUDED ALUMINUM FOR UNITS WITH EITHER WIDTH OR HEIGHT 30" OR LARGER). FRAME IS ASSEMBLED USING CORNER CLIPS TO ASSURE HAIRLINE MITERED CORNERS.

#### BLADES

0.030" THICK ROLL FORMED ALUMINUM. 1-WAY DEFLECTION. ADJUSTABLE CURVE BLADE DESIGN.

#### VANES:

DEFLECTION VANES ARE EASILY SET WITHOUT USE OF SPECIAL TOOLS.

## DAMPER:

MULTI-SHUTTER DAMPER IS EASILY ADJUSTED

#### DEPTH:

NARROW DEPTH OF DAMPER DESIGN ALLOWS GRILL/DAMPER COMBINATION TO BE USED IN STACKHEADS OF MINIMUM DEPTHS.

#### GASKET:

RUBBER GASKET IN COMPLIANCE WITH FLORIDA STATE BUILDING CODE

### OPTIONAL:

MODEL PF PLASTER FRAMES ARE AVAILABLE

## FINISH


SKY-WHITE (STANDARD) MILL FINISH (OPTIONAL)


AXALTA SKY-WHITE 100% POLYESTER POWDER COATING GIVES AN ATTRACTIVE BRIGHT WHITE FINISH AND PROVIDES ADDITIONAL PROTECTION FROM AGING AND WEAR.


## SIZES:

4" X 4" MIN 36" X 36" MAX

JOB NAME:	
LOCATION:	
ARCHITECT:	
ENGINEER:	
CONTRACTO	R:
	NTACT GRILLE TECH INC. FOR TIONAL INFORMATION OR WITH SPECIAL REQUIREMENTS.
	5101 NW 36TH AVE MIAMI, FL 33142 PHONE: 305-537-0053 FAX: 305-537-0064
	B: WWW.GRILLETECHINC.COM IL: SALES@GRILLETECHINC.COM







## **MODEL CL1M**

CURVED BLADE LOUVERED FACE 1-WAY DEFLECTION GRILLE OR REGISTER WITH MULTI-SHUTTER DAMPER

NOTE: ALL DRAWINGS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.



DRAWN BY: MR	7/14/17	NOT TO SCALE	DRAVING ND	
CHECKED BY:	7/31/17	7/14/17	CLTIVI	