

PRODUCT SPECIFICATIONS

STANDARD CONSTRUCTION

0.032" THICK, ROLL FORMED ALUMINUM (0.045" THICK EXTRUDED ALUMINUM FOR UNITS WITH EITHER WIDTH OR HEIGHT 30" OR LARGER). FRAME IS ASSEMBLED USING CORNER CLIPS TO ASSURE HAIRLINE MITERED CORNERS.

0.030" THICK ROLL FORMED ALUMINUM. 1-WAY DEFLECTION. ADJUSTABLE CURVE BLADE DESIGN.

VANES:

DEFLECTION VANES ARE EASILY SET WITHOUT USE OF SPECIAL TOOLS.

DAMPER:

MULTI-SHUTTER DAMPER IS EASILY ADJUSTED.

NARROW DEPTH OF DAMPER DESIGN ALLOWS GRILL/DAMPER COMBINATION TO BE USED IN STACK HEADS OF MINIMUM DEPTHS.

RUBBER GASKET IN COMPLIANCE WITH FLORIDA STATE BUILDING CODE.

OPTIONAL:

MODEL PF PLASTER FRAMES ARE AVAILABLE


SKY-WHITE (STANDARD) MILL FINISH (OPTIONAL)


AXALTA SKY-WHITE 100% POLYESTER POWDER COATING GIVES AN ATTRACTIVE BRIGHT WHITE FINISH AND PROVIDES ADDITIONAL PROTECTION FROM AGING AND WEAR.


SIZES:

4" x 4" MIN 36" X 36" MAX

JOB NAME:	
LOCATION:	
ARCHITECT:	
ENGINEER:	
CONTRACTOR:	
ADDITI	TACT GRILLE TECH INC. FOR ONAL INFORMATION OR WITH PECIAL REQUIREMENTS.
	5101 NW 36TH AVE MIAMI, FL 33142 PHONE: 305-537-0053 FAX: 305-537-0064
	WWW.GRILLETECHINC.COM : SALES@GRILLETECHINC.COM







MODEL CL4M

CURVED BLADE MULTI-SHUTTER 4-WAY DEFLECTION GRILLE OR REGISTER WITH MULTI-SHUTTER DAMPER

Grille tech inc. 7/14/17 NOT TO SCALE MR CL4M 7/14/17 IG 7/31/17