

FV-10NLF1	120 CFM	4" Duct
FV-20NLF1	240 CFM	6" Duct
FV-30NLF1	340 CFM	6" Duct
FV-40NLF1	440 CFM	8" Duct



WhisperLine Key Benefits:

- Remote mount in-line fan for single or multiple inlets
- Insulated housing to prevent condensation and noise
- Tapered duct adapter for easy connection
- 5 positions for installation
- Joist or truss attachment brackets included
- Suspension brackets included
- Can be used to comply with ASHRAE 62.2, LEED, IAP, California Title 24 and WA Ventilation Code

WhisperLine	FV-10NLF1			FV-20NLF1			FV-30NLF1			FV-40NLF1		
Characteristics												
Static pressure in inches w.g.	0.2	0.3	0.4	0.2	0.3	0.4	0.2	0.3	0.4	0.2	0.3	0.4
Air Volume (CFM)	120	105	82	240	225	200	340	322	302	440	421	407
Power Consumption (Watts)	36.2	35.0	33.5	55.5	53.5	51.1	95.2	93.5	91.5	136	132	130
Energy Efficiency (CFMs/Watt)	3.5			4.1			3.2			3.2		
Speed	1590			1260			1337			1150		
Current	0.31			0.46			0.86			1.10		
Power Rating (V/Hz)	120/60			120/60			120/60			120/60		

WhisperLine Installation Kits					
Model No.	Description	Inlet Grille	Backdraft Damper	Clamp	Y-Adapter
FV-NLF04G	4" Inlet Grille + Metal Plate	1 (4")	-	-	-
FV-NLF06G	6" Inlet Grille + Metal Plate	1 (6")	-	-	-
PC-NLF04S	4" Single Inlet Kit	1 (4")	1 (4")	6	-
PC-NLF06S	6" Single Inlet Kit	1 (6")	1 (6")	6	-
PC-NLF04D	4" Double Inlet Kit	2 (4")	2 (4")	12	1 (4"- 4"x 2)
PC-NLF06D	6" Double Inlet Kit	2 (6")	2 (6")	12	1 (6"- 6"x 2)
PC-NLF64D	6"-4" Double Inlet Kit	2 (4")	2 (4")	12	1 (6"- 4"x 2)
PC-NLF86Y	8"-6" Y-Adapter	-	-	-	1 (8"- 6"x 2)

