



A CSW Industrials Company

K.O. DIRT BLASTER™

Dirt and Grease Stripper

Description

K.O. DIRT BLASTER™ is a high pressure cleaner and degreaser for small condenser coils found in restaurant and food service refrigeration, air conditioning, electrical and mechanical equipment. K.O. Dirt Blaster™ strips off dirt and cooking grease without a water rinse. It contains a quick drying safety solvent and has a pleasant citrus scent. Its high dielectric strength and non-flammable formula is great for most coil cleaning applications.

Characteristics | Features

- Dissolves grease quickly
- Pressure washes small condenser coils without a water rinse
- Quick Drying/ Pleasant citrus scent
- Non-flammable
- Safety Degreaser Solvent
- No CFC's

Applications

K.O. Dirt Blaster™ quickly dissolves grease and oil on refrigeration coils, oil burner surfaces and other machine parts. K.O. Dirt Blaster™ is non conductive, so it will not short out electrical equipment such as switches, relays, circuit breakers, motors and electrical components. It is particularly effective on restaurant grease and other greasy surfaces.

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet per Case
88438	20 ounce aerosol	12	19	0.52

Instructions

READ ALL DIRECTIONS, SDS AND WARNINGS ON LABEL BEFORE USING
DO NOT USE ON HOT SURFACES, PLASTICS OR PAINT WITHOUT TESTING FIRST

Removes wax finishes.

FOR USE ON CONDENSER COILS

1. Shut off equipment.
2. Loosened debris may be pushed through coil fins or may cause dripping or staining. Place cardboard behind coil to block any loosened debris or used products.
3. Saturate condenser coil with K.O.™ Dirt Blaster.
4. Wait at least 5 minutes before starting up equipment.
5. Although K.O. Dirt Blaster™ needs no rinsing or wiping, water pressure may be used to float out debris.

FOR USE ON OIL BURNER AND ALL OTHER EQUIPMENT

1. Spray on. The heavier the dirt and grease layer, the heavier the spray.
2. For heavy films and tars, allow 5 minutes soaking time, then wipe or flush off.

For best results use only on cool surfaces.

For additional technical information, call Toll Free 1-800-231-3345

Precautions

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

WARNING!

CAUSES SKIN AND SERIOUS EYE IRRITATION

MAY CAUSE RESPIRATORY IRRITATION

HARMFUL IF SWALLOWED

KEEP OUT OF REACH OF CHILDREN

Read other precautions on back panel.

CONTAINS: Methylene chloride and d-Limonene. Contains gas under pressure; may explode if heated. Suspected of causing cancer. May cause an allergic skin reaction. May cause drowsiness or dizziness. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves and eye protection. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid breathing spray. Use only outdoors or in a well-ventilated place. Contaminated work clothing must not be allowed out of the workplace. Specific treatment (see FIRST AID section on this label). Protect from sunlight. Store locked up in a well-ventilated place. Dispose of container in accordance with local regulations.

FIRST AID: IF EXPOSED OR CONCERNED: Get medical advice. **IF SWALLOWED:** Call a doctor if you feel unwell. Rinse mouth. **IF ON SKIN:** Wash with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.



WARNING: This product can expose you to chemicals including Methylene Chloride, which is known to the State of California to cause cancer and other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

For additional information, refer to Safety Data Sheet.

Specifications

Flash Point SETA CC	None
Color	Colorless
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by **RectorSeal® LLC** · 2601 Spenwick Drive, Houston, TX 77055, USA · 800-231-3345 · Fax 800-441-0051 · rectorseal.com

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2018 RectorSeal. All rights reserved. R50192-0518