

# **Safety Data Sheet**

Issue Date 26-Jun-2013 Revision Date: 01-Oct-2017 Version 1

# 1. IDENTIFICATION

**Product Identifier** 

Product Name All-Purpose Sealant - White

Other means of identification

**SDS** # RD-0200.3000.0986

Product Code 0986 / 3000 Series

Recommended use of the chemical and restrictions on use

Recommended Use An advanced, low-VOC, All-Purpose Sealant w/ a specially formulated technology allowing

it to be exposed to water after only 2 hrs w/o washing out.

Details of the supplier of the safety data sheet

Supplier Address Red Devil, Inc. 4175 Webb Street Pryor, Oklahoma 74361 www.reddevil.com

**Emergency Telephone Number** 

Company Phone Number 918-825-5744

Fax: 918-825-5761

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

# 2. HAZARDS IDENTIFICATION

### Classification

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

The product contains no substances which at their given concentration, are considered to be hazardous to health

Appearance White paste Physical State Paste Odor Slight

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Calcium Carbonate	471-34-1	<60
Proprietary MS Polymer Blend	MIXTURE	<30
Diisodecyl phthalate	26761-40-0	<30
Vinyltrimethoxysilane	2768-02-7	<3
Titanium dioxide	13463-67-7	<10
Non-hazardous Ingredients*	Proprietary	<10
Crystalline silica	14808-60-7	<1

<sup>\*</sup> Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). (Calcium Carbonate, Titanium Dioxide) Inhalation of particulates unlikely due to product's physical state. Crystalline Silica (as Quartz) present @ low levels in Calcium Carbonate filler.

# 4. FIRST-AID MEASURES

# **First Aid Measures**

**General Advice** Provide this SDS to medical personnel for treatment.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Seek immediate medical attention/advice.

Skin Contact In case of contact, immediately wash skin with soap and water or water for at least 15

minutes. Remove and wash contaminated clothing before reuse. If irritation persists, seek

Revision Date: 01-Oct-2017

medical attention.

**Inhalation** Remove to fresh air. If breathing is difficult, leave area to obtain fresh air. If breathing

remains difficult, get medical attention.

**Ingestion** If swallowed, do not induce vomiting. Get medical attention immediately.

### Most important symptoms and effects

**Symptoms** Prolonged or repeated skin contact may result in dermatitis (red, dry skin). Direct contact

with eyes may cause temporary irritation. Exposed individuals may experience eye tearing, redness and discomfort. Irritating to mouth, throat, and stomach if ingested. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Overexposure to vapors during application and curing may mildly irritate respiratory tract and result in coughing and

sneezing.

### Indication of any immediate medical attention and special treatment needed

Notes to Physician Provide general supportive measures and treat symptomatically. May aggravate

pre-existing skin disorders.

# 5. FIRE-FIGHTING MEASURES

### **Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Small Fire** Use carbon dioxide (CO2), dry chemical or water spray.

**Large Fire** Dry chemical, Use foam or water spray.

Unsuitable Extinguishing Media Not determined.

#### Specific Hazards Arising from the Chemical

Product is combustible & may ignite if exposed to high temperature or direct flame.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

#### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Wear protective clothing as described in Section 8 of this safety data sheet.

Other Information Small Spills: 1 drum or less – Level D Equipment (gloves, chemical resistant apron, boots &

eye protection).

Large Spills: Rubber gloves, rubber boots, face shield & Tyvek suit as a minimum. Minimum level of PPE for releases in which the oxygen level is < 19.5% or is unknown, should be Level B: triple gloves (rubber gloves & nitrile gloves over latex gloves), chemical resistant suit, fire-retardant clothing & boots, hard hat & self-contained breathing apparatus.

Revision Date: 01-Oct-2017

For Emergency Responders Restrict access to spill area.

**Environmental Precautions** Minimize use of water to prevent environmental contamination. Prevent spill or rinse from

contaminating storm drains, sewers, soil or groundwater. Do not allow discharge containing

this material to enter streams, ponds, estuaries, oceans or other waters unless in

accordance w/ requirements of National Pollutant Discharge Elimination System (NPDES) permit & permitting authority has been notified in writing prior to discharge. Do not allow discharge containing this material to enter sewer systems w/o previously notifying local sewage treatment plant authority. For information, contact State Water Board or EPA

Regional Office

Other: U.S. regulations may require reporting of spills of this material reaching surface

waters if sheen is formed.

#### Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill.

Methods for Clean-Up Sweep up absorbed material and shovel into suitable containers for disposal. Wash area

with soap and water. For waste disposal, see section 13 of the SDS.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

Advice on Safe Handling Avoid breathing vapors. Use only with adequate ventilation. Open windows & doors to

ensure fresh air cross-ventilation during application and curing. Wash thoroughly with soap and water after handling. Avoid contact with skin, eyes or clothing. While handling product keep out of reach of children and pets. Do not eat or drink while handling this material. See section 6 of this SDS for clean up instructions. Remove contact lenses before using & do not handle contact lenses until all sealant has been cleaned from fingertips, nails & cuticles.

Residual sealant may transfer to contact lenses & result in severe eye irritation.

Conditions for safe storage, including any incompatibilities

Keep tightly closed in a dry and cool place. Close container after each use. Store containers away from excessive heat & freezing. Do not store @ temperatures above 120°

F. Protect from direct sunlight. Store away from incompatible materials. To maximize shelf

Revision Date: 01-Oct-2017

life, store @ temperatures below 26C (80F).

Incompatible Materials Strong bases, Strong oxidizing agents.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Guidelines**

**Storage Conditions** 

Exposure guidelines / protective equipment are for routine handling and accidental spills

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Carbonate 471-34-1	-	-	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	IDLH: 5000 mg/m <sup>3</sup>
Crystalline silica 14808-60-7	TWA: 0.025 mg/m³ respirable fraction	<ul> <li>(vacated) TWA: 0.1 mg/m³ respirable dust</li> <li>: (30)/(%SiO2 + 2) mg/m³ TWA total dust</li> <li>: (250)/(%SiO2 + 5) mppcf TWA respirable fraction</li> <li>: (10)/(%SiO2 + 2) mg/m³ TWA respirable fraction</li> </ul>	IDLH: 50 mg/m³ respirable dust TWA: 0.05 mg/m³ respirable dust

### **Appropriate engineering controls**

**Engineering Controls** 

Ventilation must be adequate to maintain the ambient workplace atmosphere below the

exposure limit(s) outlined in the SDS.

### Individual protection measures, such as personal protective equipment

**Eye/Face Protection**Use approved safety goggles or safety glasses. If necessary, refer to appropriate

regulations & standards.

Skin and Body Protection Skin: Wear chemical impervious gloves (eg: Nitrile or Neoprene). Use triple gloves for spill

response. If necessary, refer to appropriate regulations & standards.

Body: Use protection appropriate for task (eg: lab coat, coveralls, Tyvek suit). If necessary, refer to OSHA Technical Manual (Sec. VII: Personal Protective Equipment) or appropriate Standards of Canada. Use foot protection, as described in appropriate regulations &

standards.

Respiratory Protection In event of insufficient ventilation, suitable respirator should be used. NIOSH-approved air

purifying respirator w/ organic vapor canister may be necessary under circumstances of airborne concentrations exceeding exposure limits. Respirator program meeting OSHA 1910.134 & ANSI Z88.2 requirements should be followed when workplace conditions

warrant respirator use.

General Hygiene Considerations Wash hands before breaks and immediately after handling the product. Wash contaminated

clothing before reuse.

Precautionary Measures: Contact lenses may pose a hazard. Soft lenses may absorb & all

lenses may concentrate irritants.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# Information on basic physical and chemical properties

·

Revision Date: 01-Oct-2017

Physical State Paste

Appearance White paste Odor Slight

Color White Odor Threshold Not determined

Property Note: The information below is not Remarks • Method

intended for use in preparing

product specifications

pH Not applicable
Melting Point/Freezing Point < 0 °C / <32 °F
Boiling Point/Boiling Range Not applicable

Flash Point > 93.33 °C / > 200 °F CC (closed cup)

**Evaporation Rate** Slower than n-Butyl Acetate

Flammability (Solid, Gas)
Upper Flammability Limits
Not established
Lower Flammability Limit
Vapor Pressure
Vapor Density
Not established
Heavier Than air

**Specific Gravity** 1.25-1.75 @ 25 °C (77 °F)

**Water Solubility** Not Established Solubility in other solvents Not determined **Partition Coefficient** Not determined **Autoignition Temperature** Not established **Decomposition Temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined **VOC Content (%)** < 2%

VOC Content (%) < 2% VOC Content <35 g/L

# 10. STABILITY AND REACTIVITY

#### Reactivity

Cures upon contact with air.

# **Chemical Stability**

Stable under recommended storage conditions.

### **Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous Polymerization** Hazardous polymerization does not occur.

# **Conditions to Avoid**

Incompatible Materials. Excessive heat or cold.

### **Incompatible Materials**

Strong bases, Strong oxidizing agents.

# **Hazardous Decomposition Products**

No hazardous decomposition products if stored & handled as prescribed.

# 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

**Product Information** 

**Eye Contact** Eye contact may result in tearing, redness & pain.

**Skin Contact** Prolonged and frequent contact may cause redness and irritation. Repeated skin contact

may cause dermatitis.

Inhalation Overexposure to vapors during application & curing may mildly irritate respiratory tract &

result in coughing & sneezing.

May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Ingestion

### **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Calcium Carbonate 471-34-1	= 6450 mg/kg (Rat)	-	-
Diisodecyl phthalate 26761-40-0	= 64 g/kg (Rat)	> 2900 mg/kg (Rat) > 3160 mg/kg (Rabbit)	> 12.54 mg/L (Rat) 4 h
Vinyltrimethoxysilane 2768-02-7	= 7340 µL/kg(Rat)	= 3360 μL/kg(Rabbit)	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Crystalline silica 14808-60-7	= 500 mg/kg (Rat)	-	-

### Information on physical, chemical and toxicological effects

Please see section 4 of this SDS for symptoms. **Symptoms** 

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Not known to be human skin or respiratory sensitizers.

The table below indicates whether each agency has listed any ingredient as a carcinogen. Carcinogenicity

> Titanium dioxide is a possible carcinogen when it appears as a respirable dust. Crystalline Silica is considered to be a human carcinogen when in respirable form (dust / powder).

Revision Date: 01-Oct-2017

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7		Group 2B		X
Crystalline silica	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Chronic toxicity** Repeated or prolonged exposure may result in skin, respiratory, kidney & liver damage.

Prolonged & repeated skin contact may result in irritation & possibly dermatitis.

Acute: Eyes & Skin. Chronic: Skin. **Target organ effects** 

### Numerical measures of toxicity

Not determined

### 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

\_\_\_\_\_

Revision Date: 01-Oct-2017

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

### **Component Information**

Chemical Name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Diisodecyl phthalate 26761-40-0	500: 72 h Desmodesmus subspicatus mg/L EC50 0.8:			500: 24 h Daphnia magna Straus mg/L EC50 0.02: 48
	96 h Pseudokirchneriella subcapitata mg/L EC50 static	flow-through 0.55: 96 h Lepomis macrochirus mg/L LC50 static 10000: 96 h		h Daphnia magna mg/L EC50 Static
	SidilC	Leuciscus idus mg/L LC50 static		

# Persistence/Degradability

Not tested for persistence & biodegradability

### **Bioaccumulation**

Not tested for bio-accumulation potential

#### Mobility

Not tested for mobility in soil

#### **Other Adverse Effects**

Not determined

# 13. DISPOSAL CONSIDERATIONS

### **Waste Treatment Methods**

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

# 14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

**DOT** Not regulated

IATA Not regulated

IMDG Not regulated

# 15. REGULATORY INFORMATION

**International Inventories** 

TSCA Listed

Legend:

\_\_\_\_

Revision Date: 01-Oct-2017

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

### **US Federal Regulations**

# SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard No
Sudden Release of Pressure Hazard No
Reactive Hazard No

### **SARA 313**

Not determined

# **CWA (Clean Water Act)**

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Diisodecyl phthalate 26761-40-0 ( <30 )		Х		

# **US State Regulations**

### **California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65	
Diisodecyl phthalate - 26761-40-0	Developmental	
Titanium dioxide - 13463-67-7	Carcinogen	
Crystalline silica - 14808-60-7	Carcinogen	

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Diisodecyl phthalate 26761-40-0			Х
Titanium dioxide 13463-67-7	X	X	Х
Crystalline silica 14808-60-7	X	Х	Х

40 OTHER INCORMATION

# **16. OTHER INFORMATION**

Revision Date: 01-Oct-2017

NFPAHealth HazardsFlammabilityInstabilitySpecial Hazards110Not determinedHMISHealth HazardsFlammabilityPhysical HazardsPersonal Protection110X

Issue Date26-Jun-2013Revision Date:01-Oct-2017Revision NoteNew format

# **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**