


# Direct Drive Blower Motors - PSC


5½ inch dia. MARS SERIES 039



GE Commercial Motors  
By Regal-Beloit

## 5KCP39 PSC Torsion Flex Mount Motors

GE torsion-flex mount motors are designed for direct drive furnace blower applications. The unique torsion-flex mounting speeds installation while the special steel of the torsion-flex bracket absorbs vibration for quieter operation. All models are electrically reversible, 3-speed motors of high efficiency Energy Saver® design.



### Features:

- Energy Saver®
- all angle sleeve bearings
- 3-speed 1075/925/775 RPM<sup>(1)</sup>
- torsion-flex mounting, grommets and sleeves included
- 5.0 inch long, ½ inch diameter shaft
- reversible rotation

### Specifications:

- Class A insulation
- single phase, 60/50 Hertz
- overload protection
- fan duty, continuous, air over
- open construction
- 26 inch leads

### 1075 RPM<sup>(1)</sup> – Three Speed – Reversible Rotation - 6 Pole

MARS NO.	GE NO. 5KCP39	HP	VOLTS	AMPS	CAP. REQUIRED	DIMENSIONS A	DIMENSIONS B	BLOWER SIZE
03782	DGP729S	1/6	115V	2.5	5/370	5.0	4.55	9 in.
03783 <sup>(2)</sup>	GGP730S	1/4	115	3.7	7.5/370	5.0	4.23	9 in.
03784	FGP731S	1/4	208-230	1.7	5/370	5.0	4.23	9 in.
03785 <sup>(2)</sup>	LGP732S	1/3	115	4.9	7.5/370	5.0	4.98	9 in.
03786	JGP733S	1/3	208-230	2.5	5/370	5.0	4.73	9 in.
03787	PGP734S	1/2	115	7.3	10/370	5.0	5.48	10 in.
03788	NGP735S	1/2	208-230	3.5	7.5/370	5.0	5.23	10 in.
03789 <sup>(2)</sup>	PGP736S	3/4	115	9.1	15/370	5.0	5.48	10 in.
03790 <sup>(2)</sup>	PGP737S	3/4	208-230	4.4	10/370	5.0	5.48	10 in.

(1) Approximately 150RPM differential between speeds depending on fan load (2) 60 Hz only

GE by RBC



GE Commercial Motors  
By Regal-Beloit

## Ball Bearing Unit Heater Motors


GE 5KCP39 ball bearing motors are designed for unit heater applications. Each motor includes base and capacitor, and also features extended thru bolts. These electrically reversible motors are totally enclosed with a BX connector on the shell and 60 inch leads.

### Features:

- Energy Saver®
- Ball bearings
- Mounting base and capacitor included
- Totally enclosed with BX connector and extended thru bolts
- 5.0 inch long, ½ inch diameter shaft

### Specifications:

- Single phase, 60/50 Hertz
- Overload protection
- Fan duty, continuous, air over
- Totally enclosed
- 60 inch leads
- Class A insulation



### 1075 RPM – Reversible Rotation - 6 Pole

MARS NO.	GE NO. 5KCP39	HP	VOLTS	AMPS	CAPACITOR (FURNISHED)	DIMENSIONS A	DIMENSIONS B	DIMENSIONS C
03206	EGC336T	1/6	115	2.2	5/370	5.0	4.89	1/2
03208	JGC337T	1/4	115	3.3	10/370	5.0	5.14	1/2
03210	HGC338T	1/4	208-230	1.4	7.5/370	5.0	5.14	1/2
03212	NGC339T	1/3	115	4.9	10/370	5.0	6.14	1/2
03214	MGC340T	1/3	208-230	2.0	10/370	5.0	6.14	1/2



The largest selection of motors, components and accessories for the HVAC/R Industry