



PCXP AC Motor Models



PCD DC Motor Models



PCV Value Series Models



PCLP Low Profile Models



PCRL Recessed Vent Light Models

BATHROOM FAN SIZING

Based on the Home Ventilating Institute (HVI) guidelines

5′

FAN SIZING FOR BATHROOMS UNDER 100 SQUARE

FEET

The standard rule for bathrooms 100 square feet or smaller is one CFM per square foot of the bathroom. To find the square footage, multiply the length of the bathroom by the width.

9

45 sq.ft.

The minimum recommendation is a fan rated at least 45 CFM.

Ventilation for baths over 100 square feet is calculated based on the fixtures in the bathroom (see table below). Add the CFM of all fixtures within the bathroom for the required fan CFM. Enclosed toilet rooms must have an operable window or a fan for ventilation.

CFM REQUIRED PER FIXTURE

Toilet	50 CFM
Shower	50 CFM
Bath Tub	50 CFM
Jetted Tub	100 CFM

EXAMPLE

1 Toilet	50 CFM
1 Jetted Tub	100 CFM
Required CFM	150 CFM



SOLUTION

- 1. Install a 100 CFM fan over the tub, 50 CFM fan in the shower and above the toliet. This method will provide ventilation where and when it's needed.
- 2. Install one 150 CFM fan. The air will be pulled through the entire room and exhausted at a central location.

For more information on bath fan sizing and ventilation, visit www.hvi.org.

IMPROVE IAQ WITH THE PREMIUM CHOICE SERIES

Americans spend
of their time
INDOORS.







As buildings are being built with higher quality construction methods, balanced ventilation methods are more important than ever. An unbalanced home results in poor Indoor Air Quality (IAQ), causing inadequate conditions for your home and the inhabitants. As codes change, it is important for you to understand why Indoor Air Quality is so important and the options available to you from S&P USA.

Locate the best fan for your project to the right.

SERIES	MODEL	CFM	SONES +	PAGE
	PC50XP	50	0.4	8
PCXP	PC80XP	80	0.4	8
AC Motor Models	PC110XP	110	0.3	8
	PC150XP	150	0.5	8
PCD .	PCD80XH	80	1.5	10
DC Motor	PCD 110XP	110	0.3	10
Models	PCD 110XIAQS	110	0.9	10
PCRL	PCRL80	80	1.2	12
Recessed T Light	PCRL80F	80	1.2	12
PCV	PCV50	50	2.5	13
Value Series Models	PCV80	80	1.5	13
PCLP	PCLP80	80	1.2	14
Low Profile Models	PCLP100	100	2	14

PREMIUM CHOICE DIFFERENCE











LONG LIFE BEST IN CLASS WARRANTY

STRESS-FREE INSTALLATION

PLUG-&-PLAY DESIGN ENERGY EFFICIENT

PLUG-&-PLAY MODULES + GRILLES


S&P's unique Plug-&-Play options make your CHOICE easy. Whether you're looking for a Speed Control, Humidity Sensor, Motion/Humidity Sensor or VOC Sensor, there is a control that connects to the receptacle and easily mounts into the pre-drilled holes inside the fan housing.

There is a receptacle for your grille CHOICE.

Need a lighted fan? Choose the fluorescent or LED Lighted Grille Kits. Need a motion sensing fan?

Choose the Motion Sensing Grille Kit. Either grille easily plugs into the grille receptacle to give you the fan of your CHOICE!

PC Fan models include receptacles based on compatibility. Learn more in our Accessories section.



And the second s

MODULES + GRILLES

- Humidity Sensor
- Volatile Organic Compound + Humidity Sensor
- Speed Control
- Motion + Humidity Sensor
- Grille Kit
- CFL Lighted Motion Grille
- LED Lighted Grille
- Lighted Motion Grille



^{*}The receptacle for the PCIAQS is field installed.

UNDERSTANDING PLUG-&-PLAY PICK YOUR FAN

Pick a base fan from one of our Premium CHOICE Series models.

EXAMPLE: PC110XP AC Model



PICK YOUR MODULE OR GRILLE

Choose a compatible Module or Grille Kit for your custom need

EXAMPLE: PCLMHKP Lighted Motion and --Humidity Sensor Kit for PCXP Series



ORDER YOUR CUSTOM FAN

Order your Base Fan + Module/Grille to receive your full custom fan.

EXAMPLE: PC110XP + PCLMHKP



PCXP - AC MOTOR MODELS





FEATURES

- Extremely quiet operation 0.3 to 0.5 sones
- Redesigned blower for increased efficiency and lower sound
- Seamless Plug-&-Play integration
- Select models available as Contractor Packs (packs of 4)

M	ODEL	CFM	SONES ⁺
PC	C50XP	50	0.4
PC	C8OXP	90	0.4
PC	110XP	120	0.3
PC	150XP	150	0.5











exclude



HUMIDITY SENSOR **PCHSP**

SPEED CONTROL PCSCP



VOLATILE ORGANIC COMPOUND AND HUMIDITY SENSOR PCIAQSP







CFL LIGHTED GRILLE
PCLKP



LIGHTED MOTION
AND HUMIDITY
GRILLE KIT
PCLMHKP



RADIATION DAMPER
PCRD



MOTION AND HUMIDITY
GRILLE KIT
PCMHKP



LED LIGHTED GRILLE **PCLEDKP**



LED LIGHTED GRILLE
PCVLEDKP
for PC50XP



RADIATION DAMPER
PCVRD



^{*} UL certified includes 230V ONLY

⁺ Sones shown are at .1" of Static Prssure

PCXP - AC MOTOR MODELS

Fan Model	Accessory	Compatible with:
	PCSCP	
	PCHSP	PCVRD, PCVLEDKP, PCVLEDKRDP
PC50XP	PCVRD	
	PCVLEDKP	PCSCP, PCHSP
	PCVLEDKRDP	
	PCSCP	
	PCHSP	PCLKP, PCLEDKP, PCMGP, PCRD, PCLKRDP, PCLEDKRDP, PCMGKRDP
	PCIAQSP	, , , ,
	PCLKP	
	PCLEDKP	PCSCP, PCHSP, PCIAQSP
	PCMGP	
PC80XP, PC110XP, PC150XP, PCHP,	РСМНКР	NA.
PC80XFP, PC110XFP	PCLMHKP	NA NA
	PCRD	
	PCLKRDP	DOCCOR DOLLOR DOLLAGOR
	PCLEDKRDP	PCSCP, PCHSP, PCIAQSP
	PCMGKRDP	
	PCMHKRDP	NA.
	PCLMHKRDP	NA NA

WHAT IS A CONTRACTOR PACK?

Contractor Packs are broken into two packages: Housing (set of 4) and Motors + Grilles (set of 4). This allows installation flexibility for large scale projects that need to be completed in phases.

AVAILABLE ON SELECT MODELS







PCD - DC MOTOR MODELS





FEATURES



- Extremely quiet operation 0.3 to 1.5 sones
- Brushless DC motor for long life
- High/Low speed delay timer
- Built in control module with motion, humidity, speed control, and delay timer (options vary per model)
- Motion grille(purchased seperately) is required for motion sensing capability

MODEL	CFM	SONES †
PCD80XH	80	1.5
PCD 110XP	110	0.3
PCD 110XIAQS	110	0.9

MODULES + GRILLES





LED LIGHTED GRILLE **PCVLEDK**













RADIATION DAMPER **PCVRD**



FOR PCD110IAQS

CFL LIGHTED GRILLE
PCLK



LED LIGHTED GRILLE **PCLEDK**



METAL GRILLE **PCMG**



RADIATION DAMPER
PCRD



FOR PCD 110XP
CFL LIGHTED GRILLE
PCLKP



LED LIGHTED GRILLE **PCLEDKP**



METAL GRILLE **PCMGP**



MOTION GRILLE
PCMRGP



FOR PCD110XP

LIGHTED MOTION
AND HUMIDITY
GRILLE KIT
PCDLMGP



RADIATION DAMPER

PCRD



Model	Accessory	Compatible with:
	PCVLK	
	PCVLEDK]
PCD80XH	PCVLEDKRD	NA
	PCVRD	
	PCLK	
	PCLEDK	
	PCMG	
PCD110XIAQS	PCRD	NA
	PCLKRD	
	PCLEDKRD	
	PCMGKRD	1
	PCLEDKP	
	PCLKP]
	PCMGP	
	PCDLMGP	
	PCMRGP	
PCD 110XP	PCRD	NA
	PCMRGRDP	
	PCLKRDP	
	PCLEDKRDP	
	PCMGKRDP	
	PCDLMGRDP	



AUTOFLO™ FROM S&P USA

Autoflo[™] is an innovative technology that automatically adjusts the fan speed based on the actual Static Pressure in the duct system ensuring a specified amount of airflow. **Available on PCD 110XP**.

PCRL-RECESSED LIGHT MODEL



FEATURES

- Designed to look like a recessed can light
- Quiet operation 1.2 sones
- Eliminates the need for a can light and a fan in the bathroom saving time and money!

MODEL	CFM	SONES †
PCRL80	80	1.2
PCRL80F	80	1.2









MODULES

HUMIDITY SENSOR **PCHS**



SPEED CONTROL PCSC



LIGHT COVER PCRL80LC



Model	Accessory	Compatible with:	
DCDLOO DCDLOOF	PCSC	DCDLOOLC	
PCRL80, PCRL80F	PCHS	PCRL80LC	

PCV-VALUE MODELS





FEATURES

- Quiet operation 1.5 to 2.5 sones
- 4" duct connector with built-in backdraft damper
- Available as Contractor Packs (packs of 4)

MODEL	CFM	sones †
PCV50	50	2.5
PCV80	80	1.5









only

MODULES + GRILLES

HUMIDITY SENSOR PCHS



SPEED CONTROL
PCSC
PCV80 only



LIGHTED GRILLE
PCVLK



LED LIGHTED GRILLE **PCVLEDK**





Model	Accessory	Compatible with:	
	PCVRD	NA	
	PCHS	PCVRD, PCVLEDK, PCVLK	
PCV50, PCV50H, PCV50F	PCVLK	PCHS	
	PCVLEDK	PCHS	
	PCVLEDKRD	PCHS	
PCV80, PCV80H, PCV80F	PCSC	PCVRD, PCVLK, PCVLEDK,	
	PCHS	PCVLEDKRD	
	PCVRD	PCSC, PCHS	
	PCVLK	PCSC, PCHS	
	PCVLEDK	PCSC, PCHS	
	PCVLEDKRD	PCSC, PCHS	

PCLP-LOW PROFILE MODELS





FEATURES

- Low profile housing design
- Suitable for sidewall mounting
- Quiet operation 1.2 to 2.0 sones
- Available as Contractor Packs (Pack of 4)
- No ceiling radiation damper is required when wall mounted, saving time and money

MODEL	CFM	SONES +	
PCLP80	80	1.2	
PCLP100	100	2	







PCLPLEDK



OPTIONAL ACCESSORY

PCLP 4" OVAL TO 3" ROUND REDUCER

PCLPR4-3



MODULES + GRILLES

HUMIDITY SENSOR SPEED CONTROL LED LIGHTED GRILLE

PCLPHS





RADIATION DAMPER
PCLPRD



Model	Accessory	Compatible with:	
PCLP80, PCLP100, PCLPH, PCLP80F, PCLP100F	PCLPLEDK		
	PCLPRD	PCLPR4-3	
	PCLPLEDKRD		
	PCLPR4-3	everything above	

PCLPSC



DID YOU KNOW?

The Premium CHOICE Low Profile Models can be mounted in sidewalls allowing flexibility in placement in Mixed-Use buildings.

GRILLES



METAL GRILLE -

PCMG/PCMGP

Ideal for commercial applications



Motion and Humidity Sensing Grille Kit -

PCMHKP

- Automatically turns on fan when motion or humidity is sensed
- Adjustable time delay shut-off from 5 to 60 minutes
- Speed Controllable low speed if enabled



Lighted Motion and Humidity Sensing Grille Kit -

PCLMHKP

- 13 watt GU24 bulb and 4 watt night light bulb
- Automatically turns on fan when motion and/or humidity is sensed
- Adjustable time delay shut-off from 5 to 60 minutes
- Speed Controllable low speed if enabled



CFL Lighted Grille Kit -

PCLK/PCLKP

 13 watt GU24 bulb and 4 watt light bulb



LED Lighted Grille Kit-

PCLEDKP/PCLPLEDK

- 11 watt LED light
- 4100K/1100 lumens
- 2 watt LED night light setting 200 lumens



CFL Lighted Grille Kit for PC Value-

PCVLK

- 13 watt GU24 bulb
- 2700K/900 lumens
- Simple plug-in receptacle in fan housing



LED Lighted Grille Kit for PC Value -

PCVLEDK/ PCVLEDKP

- 13 watt LED light
- 4100K/1100 lumens
- 2 watt LED night light setting 200 lumens
- Can be installed with new or pre-installed fan

PLUG-&-PLAY MODULES



PCHS

PCHSP



PCLPHS

HUMIDITY SENSOR

- Detects rapid rise in humidity
- Auto-shut off timer
- Accessible sensitivity adjustment
- Meets Title 24 bathroom fan requirement





PCSC

PCSCP



PCLPSC SPEED CONTROL

- Provides seamless two speed operation without additional wiring at the wall
- Accessible speed adjustment
- High speed override
- Allows for adjustable continuous speed to meet ASHRAE 62.2



PCIAQSP

VOLATILE ORGANIC COMPOUND (VOC) AND HUMIDITY SENSOR

- Detects VOCs and/or rapid rise in humidity at the ceiling
- Speed control to run fan continuously
- Meets Calirfonia Title 24 bathroom fan requirement (CALGreen)

WALL CONTROLS OPTIONS



3-SWITCH CONTROL

PC3S

Three Rocker Combination Switch with ground screw terminals and push-in wiring



FAN/LIGHT DELAY **TIMER SWITCH** FLTD-60

- Saves energy by automatically turning exhaust fan off
- One Switch controls fan and light

ASHRAE 62.2 BATH FAN

VENTILATION CONTROL

Programmable DELAY and VENTI-

Works with ALL incandescent, CFL,

fluorescent and LED lights up to

Earn LEED and ENERGY STAR

points for enhanced exhaust

FT-622

LATION settings

ventilation

- Digital Timing circuit
- Fits single switch outlet box



ROTARY SPRING WOUND TIMER SRT-30

- Hold feature enables user to override the automatic shut-off function
- Press-on knob design ensures quick and easy installation
- CFL Compatible



PROGRAMMABLE FAN

- TIMER 24 HOURS / 7 DAYS FT247
- Hold feature enables user to override the automatic shut-off function
- Press-on knob design ensures quick and easy installation
- CFL Compatible



ELECTRONIC PUSH BUTTON TIMER

EPBT-60

- Activate by pushing the button
- 10-20-30-60 minute timer

RADIATION DAMPER KITS

GENERAL FEATURES

- 3-hour rating ceiling radiation dampers
- · Ceramic fiber with fiberglass cover fire blanket
- Roll-formed frame 22 g. galvanized steel



CFL LIGHTED GRILLE AND RADIATION DAMPER KIT PCLKRDP



LED LIGHTED GRILLE AND RADIATION

DAMPER KIT

PCLEDKRD/PCLEDKRDP



MOTION AND HUMIDITY SENSING GRILLE AND RADIATION DAMPER KIT PCMHKRDP



LIGHTED MOTION AND HUMIDITY
SENSING GRILLE AND RADIATION
DAMPER KIT
PCLMHKRDP



METAL GRILLE AND RADIATION
DAMPER KIT
PCMGKRD/PCMGKRDP



LED LIGHT KIT FOR PREMIUM CHOICE
VALUE SERIES AND RADIATION DAMPER
KIT
PCVLEDKRD/PCVLEDKRDP



LED LIGHT KIT FOR PREMIUM CHOICE
LOW PROFILE SERIES AND
RADIATION DAMPER KIT
PCLPLEDKRD



MOTION GRILLE AND RADIATION DAMPER KIT **PCMRGRDP**



LIGHTED MOTION AND HUMIDITY
SENSING GRILLE AND RADIATION
DAMPER KIT
PCDLMGRDP



PREMIUM CHOICE SERIES











LONG LIFE BEST IN CLASS

WARRANTY

STRESS-FREE INSTALLATION PLUG-&-PLAY DESIGN

ENERGY EFFICIENT



S&P USA Ventilation Systems, LLC

6393 Powers Avenue Jacksonville, FL 32217 T. 904-731-4711 • F. 904-737-8322 www.solerpalau-usa.com

S&P Canada Ventilation Products, Inc.

6710 Maritz Drive Unit #7
Mississauga, ON L5W 0A1 - Canada
T. 416-744-1217 • F. 416-744-0887
www.solerpalaucanada.com

