

Specifications

- Product** TradePro Condensate Pumps
- Application** High efficiency furnaces and humidifiers
- Purpose** This product is designed to automatically pump condensate produced by high efficiency boilers and humidifiers up to 22' vertically once the level of condensate in the tank reaches a specified level.
- Advantages**
- Metal hang tabs
 - Removable check valve
 - Overflow safety switch
 - LED indicator lights
 - Anti-vibration feet
 - Ultra-quiet pump
 - 4 inlet holes



Features	120V TP-CP-20T	230V TP-CP-20T-230
Maximum Condensate Temperatures	<ul style="list-style-type: none"> • Continuous duty 140F° • Maximum inlet temperature 160F° • Not suitable for contact with steam or gasses that exceed 160F° 	
Rated Voltage	120VAC 60Hz	230VAC 60Hz
Rated Current Draw	1.9 Amps	1.0 Amps
Input Type	USA 3-prong molded plug	NEMA 6-15 plug
Maximum Lift Height	22'	22'
Flow Rate @ Zero Head	1.6 gallons per minute	1.6 gallons per minute
Dimensions	11.8" x 5.9" x 6.7"	11.8" x 5.9" x 6.7"
Weight	5 lbs.	5 lbs.
Inlet Height from Base	4.4" (1.75" low profile)	4.4" (1.75" low profile)
Tank Capacity	1/2 gallon	1/2 gallon
Included Accessories	<ul style="list-style-type: none"> • Instruction Booklet • Metal Hang Tabs • Plug Protector • 4' Remote Shutoff Leads w/insulated terminals • Polyethelene inlet covers (3) 	
Wiring Color References	Black - Live/Hot White - Neutral Green - Ground (All installations must conform to NEC requirements)	Brown - Live/Hot Blue - Live/Hot Green/Yellow - Ground (All installations must conform to NEC requirements)

Condensate Pumps