

FOR INDUSTRY PROFESSIONALS




GERMICIDAL UV LIGHT



VIRUSES



BACTERIA





Germicidal UV Light is proven to sterilize all types of biological contaminants after just a few seconds of exposure.

STERILIZES BIOLOGICAL PATHOGENS



DISINFECTS THE AIR & HVAC SYSTEM SURFACES

The TradePro Germicidal UV light is ideal for both furnaces and air handlers. Installing the light near the coils keeps them free of mold which saves energy and extends the life of the HVAC system. It also improves indoor air quality by sterilizing airborne biological pathogens such as viruses, bacteria, and allergens.



24 VAC ELECTRONIC POWER SUPPLY



Easy to install low-voltage 24 VAC electronic power supply connects to HVAC system internal power.

Magnetic Z-Bracket for quick mounting onto metal surfaces. Base snaps off for A-plate mounting with screws.



100% 254 NM germicidal UVC spectrum lamp with Unshielded quartz hot filament. Effective for one year.



TPUVL-OS UVC LAMP

90% Standard 254 NM Germicidal UVC, 10% 185 NM Odor Oxidation. Unshielded quartz hot filament. Effective for one year.

	UV Specs TP-UV24-PRO		UVC Lamp			
Part#	TP-UV24-PRO TPUVL		Magnetic Z-Bra	acket		
UVC Lamp	100% 254 NM	C	Lamp Cable			
ovo Lump	Unshielded Quartz Hot Filament Effective 1 Year	D	Electronic Pow	ver Supply		
Part #	TP-UV24OS-PRO	e	Lamp connecte	or		
UVC Lamp	TPUVL-OS 90% Standard 254 NM Germicidal UVC 10% 185 NM Odor Oxidation Unshielded Quartz Hot Filament Effective 1 Year					B
	СОММОН					N
Dimensions	Lamp: 15"L x 0.74" Dia. Power Supply: 4.2"L x 1.8" W x 1"D			A		
Weight						
	24 VAC +/- 20%, 60 Hz, 0. 68 Amps, 16 VA		С			
(it Includes	Power Supply, 6' Lamp Cable, UV Lamp, Magnetic 'Z' Mounting Bracket, Mounting Hardware, Panel Indicator				5	
Warranty	UV Lamp: 90 Days Power Supply: 1 Year					
•	(12.0)					
-						
- -						
-					°	
					° • • •	
					° • • •	

TRADE PRO. U

PRO, UV LIGHT CROSS REFERENCE GUIDE

FOR INDUSTRY PROFESSIONALS

Why Sell TradePro Germicidal UV Lights

TradePro Germicidal UV Lights extend the life of the HVAC system and save energy by reducing biofilm on cooling coils. They also improve indoor air quality by sterilizing airborne biological contaminants such as viruses, bacteria, mold, and allergens.

UVC disinfection is a proven technology that has been used for over a century in hospitals, water treatment facilities, and agriculture.

TradePro Germicidal UV Light systems are similar in form and function to the popular Blue-Tube UV from Fresh-Aire UV.

Warranty	Kit Includes	Electrical	Weight	Dimensions		UVC Lamp	Part #	UVC Lamp	Part #	radePro
Power Supply: 1 Year	Power Supply, 6' Lamp Cable, UV Lamp, Magnetic 'Z' Mounting Bracket, Mounting Hardware, Panel Indicator	24 VAC +/- 20%, 60 Hz, 0. 68 Amps, 16 VA	Weight - 1 lb.	Lamp: 15"L x 0.74" Dia. Power Supply: 4.2"L x 1.8" W x 1"D	COMMON	TPUVL-OS 90% Standard 254 NM Germicidal UVC 10% 185 NM Odor Oxidation Unshielded Quartz Hot Filament Effective 1 Year	TP-UV24OS-PRO	TPUVL 100% 254 NM Germicidal UVC Spectrum Unshielded Quartz Hot Filament Effective 1 Year	Part # TP-UV24-PRO	radePro UV Specs

TUV-BTST TUV-BTST2	12	TUV-BTER TUV-BTER2	-1	Part Numbers	US Patent #	Warranty	Kit Includes	SI DI models Electrical	ER models Electrical	Dimensions	UV Lamp	Blue-Tube UV Specs
1 Year Lamps 2 Year Lamps	120-277 VAC	1 Year Lamp 2 Year Lamp	18-32 VAC		7,704,463	Lifetime for all parts except lamp	Power Supply, 6' Lamp Cable, UV Lamp, Magnetic 'Z' Bracket, Mounting Hardware, Panel Indicator, Installation Sticker	120-277 VAC, 50/60 Hz, 0.41 amp/120V thru 0.18amp/277V	18-32 VAC, 60 Hz, 0.68 Amps, 16 VA	Lamp: 15"L x 0.74" Dia. ER Power Supply: 4.1"W x 1.7" H x 1.8"D ST Power Supply: 5.0"W x 1.1" H x 2.4"D	254 nm germicidal UV-C, quartz hot filament	UV Specs
TUVL-115P TUVL-215P	Replacement Lamps	TUVL-115P TUVL-215P	Replacement Lamp			dure	e, UV Lamp, Magnetic 'Z' , Panel Indicator, Installation	0/277V		.7" H x 1.8"D .1" H x 2.4"D	artz hot filament	