



CRUS CAT NO. 9632

MODEL K33NVWKD-1398 HP 1/20

VOLT 115 HZ 60 AMP 0.85 PH 1

R.P.M. 1550 THERMALLY PROTECTED

INS CL B 40° C AMB MFG. NO. (XXX) U

AIR OVER CONT

CW SHAFT END REV
 BLK - LINE
 BLK - LINE

YEL → INS
 BLU → INS
 RED → INS
 ORG → INS

TO REVERSE ROTATION INTERCHANGE
 BLU & ORG LEADS
 CAP 3MFD 370 VAC

WARNING: FOLLOW ALL SAFETY INFORMATION TO REDUCE POTENTIAL ELECTRICAL SHOCK. DISCONNECT POWER BEFORE SERVICING. FOLLOW NATIONAL AND LOCAL CODES FOR GROUNDING AND INSULATE UNUSED LEAD WIRES INDIVIDUALLY.

MADE IN CHINA

CRUS

ALL DIMENSIONS ARE IN INCHES

MODEL	REF	CUSTOMER	HP	VOLTS	AMPS	HZ	RPM	ROTATION	CUSTOMER PN	
K33NVWKD-1398	--	WHOLESALE-HAC	1/20	115	0.85	60	1550	CW SHAFT END REV	9632	
SHEET NUMBER 1 OF 1	REV B	REVISION RECORD FOR: C4810-00			INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION				NIDEC MOTOR CORPORATION	
		REVISED CAPACITOR MOUNTING TO LEAD END.								
REVISION DATE		06-DEC-11			ALL DIMENSIONS ARE FOR REFERENCE ONLY UNLESS TOLERANCE IS GIVEN					
ISSUED BY		REVIEWED BY		ENGINEER APPROVED		TITLE		CODE	ITEM NO.	SIZE
J. CORONADO		M. COLLINS		M. COLLINS		ASSEMBLED VIEW		V01	778385	B

NIDEC MOTOR CORPORATION 09-Dec-11