

# Sensi<sup>™</sup> Wi-Fi Thermostat

# GIVE YOUR CUSTOMERS THE ONLY SMART THERMOSTAT BRAND TO RECEIVE A J.D. POWER AWARD.



#### **GEOFENCING**

Geofencing automatically changes temperatures based on the location of the homeowner's smartphone.



### **SMART ALERTS**

Smart alerts notify homeowners of extreme temperature or humidity levels.



### SMART HOME COMPATIBLE

Compatible with smart home platforms Apple HomeKit, Amazon Alexa and Wink.









## **EASY TO INSTALL**

No c-wire required for most installations\* plus a built-in level for easy mounting.



# **EASY TO CONNECT TO WI-FI**

Easy step-by-step guide in the app to connect to Wi-Fi.



# CONTRACTOR-ON-CALL

The Sensi app stores your contact information so when your customer needs service, you're just a tap away.



# **ENERGY SAVING FEATURES**

With features like geofencing, flexible scheduling and remote access, homeowners can save money without compromising their comfort.



#### MULTI THERMOSTAT CONTROL

Easy management for schools and light commercial applications.





# DID YOU KNOW?





"Highest in Customer Satisfaction with Smart Thermostats."

Sensi by Emerson received the highest numerical score among four brands in the J.D. Power 2016 Smart Thermostat Satisfaction Report, based on 2,509 total responses, measuring the opinion of customers who purchased a smart thermostat in the previous 12 months, surveyed September 2016. Your experience may vary. Visit Jdpower.com





# Sensi Wi-Fi Thermostat 1F87U-42WF

# **SPECIFICATIONS**

#### **ELECTRICAL RATING**

20 to 30 VAC, 50/60 Hz 1.5 Amps maximum per terminal 2.5 Amps maximum (all terminals combined)

#### STANDARD SYSTEMS

Single-stage gas, oil, electric Single-stage heat pump Multi-stage gas, oil, electric Multi-stage heat pump

#### SETPOINT RANGE

50°F to 99°F (10°C to 36°C)

#### **ACCESSORIES**

Wallplate: F61-2663 (6.75" x 4.50") Thermostat guard: F29-0198

#### **DIMENSIONS**

5.88" W x 3.75" H x 1.00" D

# RATED DIFFERENTIALS (@ 6°F / HR) Fast

Heat (conventional gas/oil/elect): Cool (central air): Heat pump (heat and cool):

Heat pump (aux):

**COMPATIBILITY** 

Conventional heating and cooling system:

Heat pump\*, heat only and cool only systems:

#### **SENSI ALERT**

High temperature: Low temperature: High humidity: Loss of heat/cool:

#### Slow Med 0.75°F 19°F

0.5°F 0.9°F 1.2°F 1.7°F 0.9°F 1.2°F 1.7°F 0.5°F 0.75°F 1.9°F

### **Power Source**

Battery (power sharing) or hardwired (c-wire)

Hardwired only (c-wire)

#### Trigger

Above 99°F Below 45°F Above 78% Temp goes up or down 5°F during cycle

#### **STORAGE**

-20° to 150°F (-29° to 65°C) 0%-90% RH non-condensing

#### **OPERATING AMBIENT**

32°F to +105°F (0°C to +41°C)

#### **OPERATING HUMIDITY**

90% non-condensing max

#### **DISPLAY TEMPERATURE RANGE**

32°F to +99°F (0°C to 37°C)

\*The Sensi thermostat provides automatic dual fuel control without an outdoor sensor. A fossil fuel kit may be added if user selectable balance point settings are desired.

# ADVANCED FEATURES

## **DUAL FUEL APPLICATIONS**

Automatic staging for heat pump/gas furnace without the need for outdoor sensor or additional equipment.

### **AUTO CHANGEOVER**

Automatically switches between heating and cooling within the set range.

## **KEYPAD LOCKOUT**

Ideal for light commercial applications lock the thermostat keypad and keep the control from the Sensi app.

#### **BACKLIT DISPLAY**

Easy-to-read screen in low light.



The app changes color to let you know at a glance whether the system is heating or cooling.

### **REMOTE ACCESS**

Set, change and program home comfort from anywhere.

# **FLEXIBLE SCHEDULING**

Program a schedule for each day of the week.

#### LOCAL WEATHER

Get easy weather updates.

#### **HUMIDITY SENSOR**

Displays indoor humidity on the thermostat and in the app.



| Model           | Program<br>Options                    |       |                      | Max Stages<br>Heat/Cool |           | Applications     |             |           |                 | Power<br>Source |                 | Selectable Performance Features |                  |                             |                    |                  |                   | Comfort & Convenience Features |                           |                 |                |                              |                  |
|-----------------|---------------------------------------|-------|----------------------|-------------------------|-----------|------------------|-------------|-----------|-----------------|-----------------|-----------------|---------------------------------|------------------|-----------------------------|--------------------|------------------|-------------------|--------------------------------|---------------------------|-----------------|----------------|------------------------------|------------------|
| Model<br>Number | Wi-Fi Control/Smart<br>Home Qualified | 7 Day | Non-<br>Programmable | Conventional            | Heat Pump | Gas/Oil/Electric | 3 Wire Zone | Millivolt | PTAC Compatible | Battery         | Hardwired (24V) | Auto Changover                  | Programmable Fan | EMR/ Early<br>Start Program | Temperature Limits | Humidity Display | Dual Fuel Control | Remote Sensor                  | Filter Change<br>Reminder | Auto DST Adjust | Keypad Lockout | Cont. Backlight<br>w/ Common | Permanent Memory |
| 1F87U-42WF      | •                                     | •     | •                    | 2/2                     | 4/2       | •                | •           |           | •               | •               | •               | •                               |                  | •                           |                    | •                | •                 |                                |                           | •               | •              | •                            | •                |



‡Thermostat has internal jumper on RC and RH. On two transformer systems, clip red jumper wire on thermostat.



**EMERSON**